





NOTES: (UNLESS OTHERWISE SPECIFIED)

1. DIMENSIONS IN INCHES
2. ALL MACHINING FLUIDS SHALL BE WATER SOLUBLE AND FREE OF SULFUR, CHLORINE AND SILICONE, SUCH AS CINCINNATI MILACRON'S CIMTECH 410 (STAINLESS STEEL)
- ③ USING A VIBRATORY TOOL MARK PART AS INDICATED
- ④ SCRIBE, ENGRAVE OR STAMP DRAWING PARTNUMBER ON NOTED SURFACE OF PART AND A THREE DIGIT SERIAL NUMBER. SERIAL NUMBERS START AT 001 FOR THE FIRST PART AND PROCEED CONSECUTIVELY. USE .07" HIGH CHARACTERS. EXAMPLE: D020188- 001. A VIBRATORY TOOL MAY BE USED.

REV.	DATE	DCN #	DRAWING TREE #
A	24 JUNE 2004	E040303-00	
v1	21 APRIL 2009	E0900107-v1	



DIMENSIONS ARE IN INCHES		NAME	DATE	 CALIFORNIA INSTITUTE OF TECHNOLOGY MASSACHUSETTS INSTITUTE OF TECHNOLOGY IGR, GLASGOW UNIVERSITY GEO 600 GROUP
TOLERANCES:		CIT/RJ	05/02	
.XX ±0.01				
.XXX ±0.005				
ANGULAR ±.25°				SYSTEM ADVANCED LIGO
MATERIAL				SUB-SYSTEM SUS
302, 304 OR 316 SSSL				NEXT ASSY ROTATIONAL ADJUSTER
FINISH				PART NAME ROTATIONAL ADJUSTER UPPER BLADE CLAMP LOWERSIDE ANGLED (3.0°)
		COMMENTS:		SIZE DWG. NO. REV.
				A D030465 V1
				SCALE: NTS SHEET 1 OF 1