


6 5 4 3 2 1



NOTES: (UNLESS OTHERWISE SPECIFIED)

- CUTTING FLUIDS TO BE WATER SOLUBLE AND FREE OF SULFUR, CHLORINE, & SILICONE.
- STEEL STAMP OR ENGRAVE THE DRAWING PART NUMBER ON NOTED FACE OF PART FOLLOWED BY 'S/N', THEN A THREE DIGIT SERIAL NUMBER. SERIAL NUMBERS TO START AT 001 FOR FIRST PART AND PROCEED IN A CONSECUTIVE MANNER TO A MAXIMUM OF 999, FOR EACH SUCCEEDING PART PRODUCED. USE 0.13 HIGH CHARACTERS. EXAMPLE: D990038-A S/N 001

		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES							LIGO CALIFORNIA INSTITUTE OF TECHNOLOGY MASSACHUSETTS INSTITUTE OF TECHNOLOGY		
		TOLERANCES: FRACTIONAL ± ANGULAR ± ANGULAR MACH ± BEND ± TWO PLACE DECIMAL ±.01		THREE PLACE DECIMAL ±.005 FINISHED SURFACE RMS BREAK CORNERS IN: OUT: .005-.010 REMOVE ALL BURRS						CAVITY BEAM DUMP HOUSING TUBE, BSC8, 2KFMYX	
		MATERIAL: 6061-T6 ALU TUBING 6" SQ, 1/4" WALL	HEAT TREAT:	FINISH:	A	DCN E990205	Conley	5-6-99	CAD FILE D990223-Adwg	SIZE DWG. NO. B D990223-A	
DWG. NO.	DESCRIPTION	USED ON:	NEXT ASS'Y: D990141	REV	DESCRIPTION	APPR'D	CHECK	DRWN	DATE	SCALE	SHEET
6	REFERENCE DRAWINGS	5	4	3	2	1	1 OF 1				