



NOTES: (UNLESS OTHERWISE SPECIFIED)

- CUTTING FLUIDS TO BE WATER SOLUBLE AND FREE OF SULFUR, CHLORINE, & SILICONE.
- STEEL STAMP OR ENGRAVE THE DRAWING PART NUMBER ON NOTED FACE OF PART FOLLOWED BY 'S/N', THEN A THREE DIGIT SERIAL NUMBER. SERIAL NUMBERS TO START AT 001 FOR FIRST PART AND PROCEED IN A CONSECUTIVE MANNER TO A MAXIMUM OF 999, FOR EACH SUCCEEDING PART PRODUCED. USE .013 HIGH CHARACTERS. EXAMPLE: D990038-A S/N 001

		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES							LIGO CALIFORNIA INSTITUTE OF TECHNOLOGY MASSACHUSETTS INSTITUTE OF TECHNOLOGY			
		TOLERANCES: FRACTIONAL ± ANGULAR ± ANGULAR MACH ± BEND ± TWO PLACE DECIMAL ±.01		THREE PLACE DECIMAL ±.005 FINISHED SURFACE RMS BREAK CORNERS IN: .005-.010 REMOVE ALL BURRS						CAVITY BEAM DUMP HOUSING TUBE, BSC8, 4KITMYHR3, 4KITMYHR4		
		MATERIAL: 6061-T6 ALU TUBING 6" SQ, 1/4" WALL	HEAT TREAT:	FINISH:					APP'R'D	CHECK	DRWN	DATE
DWG. NO.	DESCRIPTION	USED ON:	NEXT ASS'Y: D990141	REV	A DCN E990205				Conley	5-6-99	CAD FILE D990225-Adwg	SIZE DWG. NO. B D990225-A
REFERENCE DRAWINGS				ISSUE DESCRIPTION				SCALE	NTS	SHEET 1 OF 1		