

**aLIGO ISC Optics: 2" High Reflector @ 532nm**

APPROVALS	DATE	RE V	DCN NO.	BY	CHECK	DCC	DATE
AUTHOR: L. BARSOTTI	10-27-2010						
CHECKED:							
APPROVED: P.Fritschel							
DCC RELEASE							

**1 Description**

2" Ø Flat/Flat high reflectors @ 532nm

**2 Material**

Corning HPFS 7980 (high purity fused silica, UV grade)  
Grade 1G

**3 Dimensions**

2"Ø +.000/-.005" X .375" ± .020" tk., Plano / Plano

**4 Surface Roughness****Side 1**

Super polish

Surface Roughness: <1Å RMS in CA

Surface Quality: 10-5

**Side 2**

Commercial Polish

Surface Roughness: <5Å RMS in CA

Surface Quality: 40-20

**5 Surface Figure****Side 1**

Flat <  $\lambda/10$  at 632.8 over central 80%

**Side 2**

Flat <  $\lambda/4$  at 632.8 over central 80%

**6 Coating**

Wavelength: 532nm

Angle of incidence: 45°

**Side 1**

R>99.99% (best effort), both for S and P polarization



## SPECIFICATION

**aLIGO ISC Optics: 2" High Reflector @ 532nm****Side 2**

AR coating,  $R < 0.5\%$  (best effort), both for S and P polarization

Serial numbers and registration marks shall be scribed or etched on the barrel of the optic for in-vacuum use

**Coating vendor to provide:**

1. Three spectrophotometer graphs of the reflectance and transmittance of the HR coatings; one covering the spectrum from 500nm to 1200nm; the others, with increased sensitivity, showing wavelengths from 900nm to 1100nm and from 500nm to 600nm
2. Spectrophotometer graphs of the reflectance of the AR coating taken as cited above.