



SPECIFICATION

aLIGO ISC Optics:

2" High Reflectors @ 1064nm

APPROVALS	DATE	RE V	DCN NO.	BY	CHECK	DCC	DATE
AUTHOR: L. BARSOTTI	01-18-11						
CHECKED:							
APPROVED: P.FRITSCHEL							
DCC RELEASE							

1 Description

2" Ø Flat/Flat high reflector @ 1064nm

2 Material

Corning HPFS 7980 1-G

3 Dimensions

1"Ø +.000/-.005" X .375" ± .020" tk., Plano / Plano

4 Surface Roughness

Side 1

Super polish

Surface Roughness: <1Å RMS in CA

Surface Quality: 10-5

Side 2

Commercial Polish

Surface Roughness: <5Å RMS in CA

Surface Quality: 40-20

5 Surface Figure

Side 1

Flat < λ/10 at 632.8 over central 80%

Side 2

Flat < λ/4 at 632.8 over central 80%



SPECIFICATION

aLIGO ISC Optics:**2" High Reflectors @ 1064nm****6 Coating**

Wavelength: **1064nm**

Angle of incidence: $45^{\circ} \pm 5^{\circ}$ (best effort for wider AOI range)

Side 1

R \geq 99.995% @ 1064nm (best effort) for **s** and **p**-polarization

Side 2

AR coating, R < 1% @ 1064nm (best effort) for **s** and **p**-polarization

Serial numbers and registration marks shall be scribed or etched on the barrel of the optic for in-vacuum use

Coating vendor to provide:

1. Three spectrophotometer graphs of the reflectance and transmittance of the HR coatings; one covering the spectrum from 500nm to 1200nm; the others, with increased sensitivity, showing wavelengths from 900nm to 1100nm and from 500nm to 600nm
2. Spectrophotometer graphs of the reflectance of the AR coating taken as cited above.