







REV.	DATE	DCN #	DRAWING TREE #

- NOTES CONTINUED:**
- SCRIBE, ENGRAVE, OR MECHANICALLY STAMP (NO INKS OR DYES) DRAWING PART NUMBER AND REVISION ON NOTED SURFACES FOLLOWED ON THE NEXT LINE BY A THREE DIGIT SERIAL NUMBER. SERIAL NUMBERS START AT 001 FOR THE FIRST PARTICLE AND PROCEED CONSECUTIVELY. USE 07 HIGH CHARACTERS. EXAMPLE: DXXXXXX.VY.5N.001. VIBRATORY TOOL MAY BE USED.
 - APPROXIMATE WEIGHT - X.XXX LB.
 - MACHINE ALL SURFACES TO REMOVE OXIDES AND MILL FINISH. USE OF ABRASIVE REMOVAL TECHNIQUES IS NOT ALLOWED. REFER TO LIGO D990034.
 - ALL PARTS SHALL BE MANUFACTURED IN ACCORDANCE WITH LIGO SPECIFICATION D990034.
 - ALL HELI-COIL HOLES TO BE PREPARED ACCORDING TO EMHART HELI-COIL PRODUCT CATALOG HC2000, REV 4.
 - ALL HELI-COIL INSERTS TO BE INSTALLED BY LIGO PERSONNEL AFTER DELIVERY OF FINISHED PARTS. USE NITRONIC-60 THREADED INSERTS.
 - ALL MATERIAL IS TO BE VIRGIN MATERIAL (i.e. NO WELD REPAIRS, PLUGS OR RECYCLED MATERIAL). NO REPAIRS SHALL BE MADE UNLESS APPROVED IN ADVANCE, AND IN WRITING, BY LIGO LABORATORY. REFER TO LIGO D990034.
 - SURFACE FINISH TO BE AS-PROCESSED FROM MILL/SUPPLIER, FREE FROM SCRATCHES OR GOUGES.
 - PART WILL BE PORCELAIN COATED PER LIGO SPECIFICATION E1000083 AFTER FABRICATION. THE INDICATED HOLES WILL BE MASKED PRIOR TO PORCELAIN COATING TO APPROXIMATELY 2.5-3X HOLE DIAMETER CENTERED ON BOTH SIDES OF THE HOLE.
 - DIMENSIONS APPLY BEFORE PORCELAIN COATING UNLESS SPECIFIED.
 - BEND RADIUS: UNLESS OTHERWISE NOTED, THE BEND RADIUS SHOULD BE THE MINIMUM REQUIRED TO FORM WITHOUT CRACKING OR REQUIRING ADDITIONAL WORK WHEN FORMING. IN PARTICULAR IF SHEET METAL IS TO BE PORCELAIN COATED, THE BEND RADIUS SHALL BE A MINIMUM OF .12" OUTSIDE RADIUS OF BEND UNLESS OTHERWISE NOTED.
 - NOTES 13 and 14 DO NOT APPLY TO THIS PART



BILL OF MATERIALS				
ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	LENGTH
1	TICOR #TS0125-1 (TS0149-25CG20BS4-100F) or EQUIVALENT	CUSTOM DB25 MALE CONNECTOR (J1) FOR UHV (GOLD METALIZED PEEK)	1	
2		CUSTOM DB25 CONNECTOR BACKSHELL FOR UHV (STAINLESS)	1	
3		QPD FEMALE CONNECTOR (J2,J3) FOR UHV (PEEK)	2	
4	C1	6 COND. CABLE WITH (5) COPPER BRAID (SHIELD) AND (6) PEEK OVERBRAID INCLUDING 6EA. 28GA. WIRES WITH C21105 PFA INSULATION	2	68in. ± 80in.
5	COPPER BRAID CONTINENTAL PART #24x3x40BC	CONTINENTAL CORDAGE PART # 24x3x40BC	2	68in. ± 80in.
6	PEEK BRAID PART #6759	PART #6759 MANUFACTURED WITH ZEUS 0.016" BLACK PEEK DRAWN MONOFILAMENT	2	68in. ± 80in.
7	PARKER# 4 TIZ. 188-SS	1/4" TUBE INSERT 1/4" LENGTH 0.188" o.d.	2	
8	GLENAIR # 600-052 or BAND-IT # A10086	GLENAIR #600-052 STANDARD BRAID CLAMP or BAND-IT PART # A10086 (0.240" WIDE) ("BAG OF 100" #A10089)	2	
9	GLENAIR # 600-057 or BAND-IT # A31186	GLENAIR #600-057 STANDARD BRAID CLAMP or BAND-IT PART # A31186 (0.120" WIDE) ("BAG OF 100" #A31189)	2	
10	HELICOIL #1185-04EN336	#4-40 Nitronic 60® HELICOIL 0.336" LENGTH	2	

- * NOTE: USE WHATEVER LENGTH IS NECESSARY FOR THE INTERNAL WIRING OF THE CONNECTORS AND STRIP LENGTH TO ACHIEVE THE CORRECT OVERALL LENGTHS.
- NOTES: (UNLESS OTHERWISE SPECIFIED)
- A. MATERIAL: a. J1 CONNECTOR SHELL - GOLD OVER ELECTRO-LESS NICKEL SELECTIVELY METALIZED PEEK VICTREX 450GL30. b. BACKSHELL - STAINLESS STEEL WITH VENT HOLE. c. CONTACTS - BERYLLIUM COPPER ALLOY C17300 0.000950 MIN. GOLD OVER NICKEL. d. HARDWARE - STAINLESS STEEL, PASSIVATED. e. PEEK BRAID - PEEK VICTREX GRADE IDS-450CA30 CARBON LOADED - SUPPLIED BY LIGO.
- B. CABLE 6 COND. 28 AWG. (40 STRD 44 AWG.) WITH C21105 PFA INSULATION. OVERALL 40AWG COPPER BRAID 90% COVERAGE - SUPPLIED BY LIGO. OVERALL PEEK BRAID MIN. 50% COVERAGE - SUPPLIED BY LIGO. OVERALL CABLE O.D. WILL BE APPROX. 0.240 IN.
- C. CONNECTORS WILL BE SUPPLIED WITH HARDWARE. SCREWS SHOULD BE THE PROPER LENGTH FOR MATING.

V25T CABLE ASSEMBLY CIRCUIT SUMMARY									
V-DB25 M/S1-68,80-2_QPD									
FROM					TO				
CONNECTOR J1 - 25 PIN SUBMINI_D MALE CONNECTOR SELECTIVELY METALIZED (PEEK)					CONNECTOR J2 - QPD FEMALE CONNECTOR (PEEK)			PCB CONNECTION	
PIN	WIRE NAME	COLOR	LENGTH	TWISTED PAIR	PIN	WIRE NAME	SIGNAL		
1,SHELL	SHIELD (BRAID)		68in.		CONNECTED ONLY TO BRAID CLAMP	SHIELD (BRAID)	SHIELD	N/C	
13	(CABLE 1) WIRE 13	White	68in. *	TP-1	A4	(CABLE 1) WIRE 13	QPD 1 ANODE 4	A4	
25	(CABLE 1) WIRE 25	White	68in. *		A3	(CABLE 1) WIRE 25	QPD 1 ANODE 3	A3	
12	(CABLE 1) WIRE 12	White	68in. *		A2	(CABLE 1) WIRE 12	QPD 1 ANODE 2	A2	
24	(CABLE 1) WIRE 24	White	68in. *		A1	(CABLE 1) WIRE 24	QPD 1 ANODE 1	A1	
11	(CABLE 1) WIRE 11	White	68in. *		S	(CABLE 1) WIRE 11	QPD 1 SENSE	S	
23	(CABLE 1) WIRE 23	White	68in. *		CAT	(CABLE 1) WIRE 23	QPD 1 CATHODE	CAT	
					CONNECTOR J3 - QPD FEMALE CONNECTOR (PEEK)			PCB CONNECTION	
					PIN	WIRE NAME	SIGNAL		
1,SHELL	SHIELD (BRAID)		80in.		CONNECTED ONLY TO BRAID CLAMP	SHIELD (BRAID)	SHIELD	N/C	
10	(CABLE 2) WIRE 10	White	80in. *		A4	(CABLE 2) WIRE 10	QPD 2 ANODE 4	A4	
22	(CABLE 2) WIRE 22	White	80in. *	TP-4	A3	(CABLE 2) WIRE 22	QPD 2 ANODE 3	A3	
9	(CABLE 2) WIRE 9	White	80in. *		A2	(CABLE 2) WIRE 9	QPD 2 ANODE 2	A2	
21	(CABLE 2) WIRE 21	White	80in. *		A1	(CABLE 2) WIRE 21	QPD 2 ANODE 1	A1	
8	(CABLE 2) WIRE 8	White	80in. *	TP-5	S	(CABLE 2) WIRE 8	QPD 2 SENSE	S	
20	(CABLE 2) WIRE 20	White	80in. *		CAT	(CABLE 2) WIRE 20	QPD 2 CATHODE	CAT	
PIN 14,2,15,3,16,4,17,5,18,6,19,7 N/C (NOT CONNECTED)									
* USE WHATEVER LENGTH IS NECESSARY FOR THE INTERNAL WIRING OF THE CONNECTORS AND STRIP LENGTH TO ACHIEVE THE CORRECT OVERALL LENGTHS. * INCLUDE NOM. 68 or 80in. LENGTH + STRIP LENGTH + INTERNAL SERVICE LOOPS + 6in. FOR PIGTAILS.									

TEST LIST	
FROM	TO
J1	J2
PIN	PIN
J1 - 1,SHELL	NOT CONNECTED
J1 - 13	J2 - A4
J1 - 25	J2 - A3
J1 - 12	J2 - A2
J1 - 24	J2 - A1
J1 - 11	J2 - S
J1 - 23	J2 - CAT
J1	J3
PIN	PIN
J1 - 1,SHELL	NOT CONNECTED
J1 - 10	J3 - A4
J1 - 22	J3 - A3
J1 - 9	J3 - A2
J1 - 21	J3 - A1
J1 - 8	J3 - S
J1 - 20	J3 - CAT

V-DB25 M/S1-68,80-2_QPD		
STANDARD USE FOR THIS CABLE		
SUBSYSTEM	AIR/VAC	STANDARD USE
ISC	IN-VAC	OPD'S FOR TRANSMON

NOTES AND TOLERANCES (UNLESS OTHERWISE SPECIFIED)

1. INTERPRET DRAWING PER ASME Y14.5-1994.

2. REMOVE ALL SHARP EDGES. 100% OILS FOR MACHINED PARTS. ROUND ALL EDGES APPROXIMATELY R.02 FOR SHEET METAL PARTS.

3. DO NOT SCALE FROM DRAWING.

4. ALL MACHINING FLUIDS MUST BE FULLY SYNTHETIC, FULLY WATER SOLUBLE AND FREE OF SULFUR, SILICONE, AND CHLORINE.

DIMENSIONS ARE IN INCHES

TOLERANCES:

XXX ±

ANGULAR ±

MATERIAL: Material <not specified>

FINISH: μinches

NEXT ASSY

CALIFORNIA INSTITUTE OF TECHNOLOGY MASSACHUSETTS INSTITUTE OF TECHNOLOGY

PART NAME: CUSTOM CABLE SPECIFICATION V25T-68-80

DESIGNER: R. ABBOTT DATE: 06/10/2012 SITE: DWG. NO.

DRAWER: E. BROWN DATE: 06/10/2012 SITE: E D1101624

CHECKER: APPROVAL: SCALE: 2:1 PROJECTION: SHEET 1 OF 1