

LASER INTERFEROMETER GRAVITATIONAL WAVE OBSERVATORY
- LIGO -
CALIFORNIA INSTITUTE OF TECHNOLOGY
MASSACHUSETTS INSTITUTE OF TECHNOLOGY

Technical Note	LIGO-T1800475-v2	2019/05/17
Phase noise analysis of the Coherent Audio/Locking Fields for squeezing characterization		
L. McCuller		

Distribution of this document:

LVC

California Institute of Technology
LIGO Project, MS 18-34
Pasadena, CA 91125
Phone (626) 395-2129
Fax (626) 304-9834
E-mail: info@ligo.caltech.edu

Massachusetts Institute of Technology
LIGO Project, Room NW17-161
Cambridge, MA 02139
Phone (617) 253-4824
Fax (617) 253-7014
E-mail: info@ligo.mit.edu

LIGO Hanford Observatory
Route 10, Mile Marker 2
Richland, WA 99352
Phone (509) 372-8106
Fax (509) 372-8137
E-mail: info@ligo.caltech.edu

LIGO Livingston Observatory
19100 LIGO Lane
Livingston, LA 70754
Phone (225) 686-3100
Fax (225) 686-7189
E-mail: info@ligo.caltech.edu

<http://www.ligo.caltech.edu/>

1 New Layout

By adjusting the injection site of the CAF, the actuation on the CLF-B VCO can then also drive the CAF frequency, imprinting the pump phase and the CLF-fiber phase into the CAF signal. An additional mixer is needed as the CAF must now be referenced from the 203 MHz squeezer signal. As far as I can tell, all workable alternative configurations also need the extra mixer and phase reference to the 3.125MHz master oscillator.




Figure 1: Signal Flow analysis of phase noise in the CLF and CAF loops with the modified CAF layout.

Which corresponds to the open loop couplings (only CAF has changed).

$$S_{\text{CLF1F}} = \hat{N}_{\text{CLF-B}} + A_{\text{CLF-B}} - \hat{N}_{\text{CLF-A}} + \hat{N}_{\text{CLF-F}} - \hat{N}_{\text{IFO}} + A_{\text{SQZ}} \quad (1)$$

$$S_{\text{CLF2F}} = \hat{N}_{\text{CLF-B}} + A_{\text{CLF-B}} - \hat{N}_{\text{CLF-A}} + \hat{N}_{\text{CLF-F}} - \hat{N}_{\text{pump}} \quad (2)$$

$$S_{\text{CAFPLL}} = -\hat{N}_{\text{CLF-A}} + \hat{N}_{\text{CAF}} + A_{\text{CAF}} \quad (3)$$

$$S_{\text{CAF1F}} = \hat{N}_{\text{CLF-B}} + A_{\text{CLF-B}} + \hat{N}_{\text{CLF-F}} - \hat{N}_{\text{CAF}} - A_{\text{CAF}} - \hat{N}_{\text{IFO}} + A_{\text{SQZ}} \quad (4)$$

$$S_{\text{SQZ}} = \hat{N}_{\text{pump}} - \hat{N}_{\text{IFO}} + A_{\text{SQZ}} \quad (5)$$

Now skipping to the closed loop equations:

$$S_{\text{CAFPLL}} = \frac{1}{1 + G_{\text{CAF}}}(-\hat{N}_{\text{CLF-A}} + \hat{N}_{\text{CAF}}) \quad (6)$$

$$S_{\text{CAF1F}} = +\hat{N}_{\text{CLF-B}} - G_{2\text{F}}S_{\text{CLF2F}} + \hat{N}_{\text{CLF-F}} - \hat{N}_{\text{CAF}} + G_{\text{CAF}}S_{\text{CAFPLL}} - \hat{N}_{\text{IFO}} - G_{1\text{F}}S_{\text{CLF1F}} \quad (7)$$

$$(8)$$

which in the limit of infinite $G_{2\text{F}}$, becomes

$$S_{\text{CAFPLL}} = \frac{1}{1 + G_{\text{CAF}}}(-\hat{N}_{\text{CLF-A}} + \hat{N}_{\text{CAF}}) \quad (9)$$

$$S_{\text{CAF1F}} = \hat{N}_{\text{CLF-A}} - \hat{N}_{\text{CAF}} + G_{\text{CAF}}S_{\text{CAFPLL}} - G_{1\text{F}}S_{\text{CLF1F}} + \hat{N}_{\text{pump}} - \hat{N}_{\text{IFO}} \quad (10)$$

or, fully reduced:

$$S_{\text{CAF1F}} = \frac{1}{1 + G_{\text{CAF}}}(\hat{N}_{\text{CLF-A}} - \hat{N}_{\text{CAF}}) + \frac{1}{1 + G_{1\text{F}}}(\hat{N}_{\text{pump}} - \hat{N}_{\text{IFO}}) \quad (11)$$

which properly shows the residual noise in the interferometer loops, as desired for the CAF.